

# NODER IO16RS

## Extension module



### Characteristic

<b>TYPE</b>	IO16RS
<b>COMPATIBLE CONTROLLERS</b>	Noder EE12 Noder EWE4
<b>NUMBER OF SUPPORTED FLOORS</b>	16
<b>NUMBER OF EXTENSIONS PER CONTROLLER</b>	1-4
<b>NUMBER OF EXTENSIONS PER ELEVATOR</b>	1-4
<b>NUMBER OF SUPPORTED FLOORS PER SINGLE CONTROLLER</b>	1-64

### Technical Specifications

<b>NUMBER OF PROGRAMABLE OUTPUTS</b>	16
<b>MAXIMUM CURRENT PER OUTPUT</b>	1 A
<b>NUMBER OF PROGRAMABLE INPUTS</b>	16
<b>COMMUNICATION WITH CONTROLLER</b>	1x RS-485
<b>POWER SUPPLY</b>	12 VDC
<b>CURRENT CONSUMPTION</b>	typically ~200 mA (max. ~337 mA)
<b>DIMENSIONS</b>	122 x 90 x 23 mm (4.8 x 3.54 x 0.91 in.)
<b>WEIGHT</b>	300 g (0.66 lb)
<b>WORKING TEMPERATURE</b>	-10 °C - +55 °C
<b>STORAGE TEMPERATURE</b>	-20 °C - +70 °C
<b>AMBIENT HUMIDITY</b>	<80%

Manufacturer: NODER S.A.  
5h Olszanska Street  
31-513 Cracow, Poland  
[www.noder.pl/en](http://www.noder.pl/en)