

RCP-1 Reader

Datasheet



 T&A reader

 Power over Ethernet (PoE)

 10" LCD touch screen

NODER S.A.
Olszańska 5H street
31-513 Cracow, Poland

www.noder.pl/en

Time and Attendance terminal

Characteristic	
COOPERATION WITH CONTROLLERS	NODER EE12 NODER EWE4 NODER EWE4-LCD
COMMUNICATION INTERFACE	RJ-45

Technical Specifications	
RFID STANDARDS	MIFARE Classic, MIFARE DESFire
FREQUENCY	13,56MHz
MAXIMUM READING RANGE	up to 4cm
SUPPLY VOLTAGE	12V DC/2A (passive PoE)
ENERGY CONSUMPTION	11W
SCREEN SIZE	10" (216,96 x 135,6mm)/(8,54 x 5,34in)
SCREEN RESOLUTION	1920 x 1080
SCREEN PROPORTIONS	16:10
SCREEN BRIGHTNESS	450cd/m ²
NUMBER OF STORED EVENTS	16,7M
VIEWING ANGLES	178°
CONTRAST	800:1
TOUCH TECHNOLOGY	Projected Capacitive
COMMUNICATION INTERFACE	10/100 Ethernet
MEMORY SIZE	16GB
WEIGHT	1,15kg (2,54lb)
DIMENSIONS	237,7 x 189,7 x 30,2mm (9,36 x 7,47 x 1,19in)
VESA STANDARD	75 x 75mm (2,95 x 2,95in)
BUZZER	built-in
VISUAL SIGNALING	yes
COLOUR	black
WORKING TEMPERATURE	0°C - +50°C
STORAGE TEMPERATURE	-30°C - +60°C
AMBIENT RELATIVE HUMIDITY	10% - 80%
NORMS	CE